

HOLLAND FW351/FW342 SERIES

THE WORLD'S
MOST VERSATILE
FIFTH WHEEL

FW351 pro-hitch



FW342 LowLube™





FW351 PRO-HITCH FW342 LowLube™

CAPACITY

- 190 kN D-Value
- Top Plate Weight = 108 kg

WARRANTY:

- 36 Months Materials and Workmanship Warranty
Not suitable for Livestock Applications

THE WORLD'S MOST POPULAR FIFTH WHEEL.

The Holland FW351 Series is the most popular fifth wheel in the world. This premium fifth wheel is designed for years of guaranteed performance, and has been the foundation for evolutionary new ideas that expand fifth wheel function and value. Available in a wide variety of models, the FW351 and FW342 meets the needs of the transportation industry for today and beyond.

FW342 LowLube™

FW342 ratings as per standard FW351 assembly specifications. The Long life replacement lube plate inserts provide friction-free performance. The lube plates fit into cast recesses of the top plate and are secured by bolts & locknuts.

PRECISION MACHINED CAST STEEL TOP PLATE

and lock mechanism fit-up maximises surface contact area, reduces friction and uneven wear and extends service life.

BRACKET PIN DESIGN

permits easy top plate removal-for reduced maintenance cost and time.




POCKET INSERTS fit between the top plate and brackets to provide long lasting top plate articulation without lubrication.



FW351 pro-hitch



FW342 LowLube™



- 1 High Coupling Protection.** Lock system protects against coupling at an improper height.
- 2 Greater Kingpin-to-Lock Jaw Contact Area.** Lock jaw contact area is 46cm²-up to 87% greater contact area over competitive models, for longer kingpin and lock life.
- 3 Forged/Cast Steel Locks.** Lock jaws are forged, machined and hardened cast steel which provide 48cm² kingpin contact area.
- 4 Precision machining** of lock mechanism/kingpin interface.




THE ERGONOMIC (FW342 SERIES) RELEASE HANDLE

features Holland's easy-to-pull, one-hand operation "trigger lock".



ACCESSIBLE GREASE FITTING AND LUBE TUBE permits easy lock lubrication.

FW2 1:21 Rev D 0408 Amendments and errors reserved. © SAF-HOLLAND (Aust.) Pty. Ltd.



B-DOUBLE HANDLE OPTION
When uncoupled release handle does not protrude past the casting width. The maximum width dimension including foot pin heads is 915mm.



ELI™
SYSTEM OPTION automatically starts when the engine starts. It immediately diagnoses the coupling status without any need for driver input. The diagnosis appears as icons in a display box.



Pneumatic Cylinder
THE HOLLAND IN-CAB AIR RELEASE SYSTEM OPTION
The driver can quickly and safely control the uncoupling process from inside the cab, improving driver efficiency and comfort. And, it helps drivers avoid the strain and mess associated with manual coupling.

SAF-HOLLAND (Aust.) Pty. Ltd. · PO Box 63 · 115 High St · Melton Vic 3337
Tel: (03) 9743 6799 Fax: (03) 9743 6763

Western Australia · Tel: (08) 9353 1720 Fax: (08) 9353 1730
Queensland · Tel: (07) 3375 7033 Fax: (07) 3375 7044
New South Wales · Tel: (02) 9672 1950 Fax: (02) 9672 1994
South Australia · Tel: (08) 8345 1546 Fax: (08) 8345 0985