




PH-30SA41

PH-30SA41 SPECIFICATIONS

Replaces part number PH-T-100-A



Weight: 32 lbs.

Patent Pending

Swivel type pintle hook with spring cushion. Swivel action provides some torsional relief and spring cushion provides some shock absorption at the coupling.

**6,000 lbs. Maximum Vertical Load
30,000 lbs. Maximum Gross Trailer Weight**

Note: In configurations where the Maximum Vertical Load does not exceed 4,000 lb. the Maximum Gross Trailer Weight is 40,000 lbs.

Tested in accordance with SAE J847 (Type II)

IMPORTANT SAFETY INFORMATION:

Maintain adequate vertical (tongue) load to properly control the trailer (generally 10%) but do not exceed the above rated capacities.

DO NOT damage the latch. Be particularly careful with the drawbar when coupling and uncoupling.

Other steps and inspections are also required. Consult OSHA and D.O.T. regulations and American Trucking Association for complete coupling and uncoupling procedures. These cover items such as cargo securement, brakes, lights, safety chains, and other important requirements.

This equipment must not be used or maintained in a careless manner.

GENERAL INFORMATION

1. Do not modify or add to the product.
2. Wear safety goggles during installation, removal and servicing.
3. Never strike any part of the pintle hook.
4. Do not weld on this product.

This product is covered by Holland's Commercial Products Warranty. Holland reserves the right, without giving prior notice, to change specifications and dimensions as designs are altered or improved.

TOWING APPLICATIONS

Trailer and equipment designed for over-the-road towing within the stated capacities. Use ONLY with a non-swivel type drawbar. For off-road applications, reduce the capacities above by 25%. This pintle hook is well suited for use in the utility and construction industries.

DRAWBAR EYE DIMENSIONS


2" to 3" I.D. with 1.25" to 1.63" diameter section.

MOUNTING


1. Use a mounting structure of sufficient strength to support the rated capacity of the pintle hook in accordance with SAE J847 and SAE J849.
2. Use the hole pattern described on the reverse.
3. Remove cotter pin (XB-T-60), nut (XB-T-9N), washer (XA-T-56), spring (XB-T-52) and both flanges (XA-10802-R and XA-10802-F).
4. Install flanges using (6) 1/2" Grade 8 fasteners. Tighten fasteners only finger tight. Slip the hook body (XA-10798) into flanges; this will align the flange bores. Properly tighten the (6) bolts to minimum torque of 60 ft-lb. Verify hook body (XA-10798) swivels freely.
5. Install spring (XB-T-52), washer (XA-T-56), and nut (XB-T-9N). Tighten nut until snug against the spring. Turn nut an additional 1/2 turn minimum and install cotter pin (XB-T-60) in the nut castellation. Spread cotter pin.

OPERATING INSTRUCTIONS

1. Before operating, inspect for proper operation, worn, damaged or missing parts and secure mounting. Correct as required before use.
2. Make sure the pintle is in the proper coupling position as shown (latch on top).
3. Open the latch (XA-10632) by lifting the lock handle (A).
4. Position the drawbar eye over the horn of the pintle and lower into place.
5. Push the latch closed. When locked, the lock handle (A) will rotate and move up until it is flush with the top of the latch (see illustrations at right).



CORRECT




INCORRECT

6. If main lock does not engage when attempting to close latch, do not force it closed by striking. Check bottom of latch and top of horn and lock seating notch on pintle body that they are free of debris.

MAINTENANCE

For proper performance, the following maintenance steps should be performed every 30,000 miles or 3 months, whichever comes first.

1. Clean and inspect for worn, damaged or missing parts. Replace as required using only Holland parts.
2. Inspect the hook (XA-10798) and latch (XA-10632 sub-assembly) in areas where contact is made with the drawbar for excessive wear. Replace the hook when wear exceeds $3/16"$ (0.188") from the original surface profile.
3. With the latch closed, measure the gap between the hook and the latch while lifting up on the latch. Replace the latch (XA-10632 sub-assembly) when the gap exceeds $1/4"$ (0.250"). See Detail A.
4. Periodically disassemble to inspect for wear on the shank and mounting brackets. Replace any component when wear exceeds $1/8"$ (0.125") from the original surface profile.
5. Regularly lubricate latch pivot with a light oil lubricant. Apply a small quantity of grease through the grease fittings in the mounting brackets.
6. Check mounting fasteners for proper torque. Retighten nut (XA-T-9N) as instructed in Step 5, of the "Mounting" instructions on page 1.



SAF-HOLLAND USA, Inc.
888.396.6501 Fax 800.356.3929

SAF-HOLLAND Canada Limited
519.537.3494 Fax 800.565.7753
Western Canada
604.574.7491 Fax 604.574.0244

SAF-HOLLAND International, Inc.
616.396.6501 Fax 616.356.1511